


# Regatta DWARF Assembly Instructions



NOMINAL SIZE	A (mm)	B (mm)
5 x 6	1654	1990
5 x 8		2610
5 x 10		3230
5 x 12		3850

NOMINAL SIZE	A (mm)	B (mm)
6ft extension	-	1860
8ft extension		2480
10ft extension		3100
12ft extension		3720



Thank you for purchasing your new Robinsons greenhouse. We recommend you familiarise yourself with the instructions and read all safety information before you commence assembly. This instruction manual is also available online at [www.robinsonsgreenhouses.co.uk](http://www.robinsonsgreenhouses.co.uk) in our technical help section should you need to reprint it. Should you require any additional advice you can always call us on 01782 385409.

These instructions are divided into sections highlighted by a white number/letter on a black background at the bottom corner of most pages (see opposite page for details); **part lists**, **B**-base, **P**-preparation, **1**-sides, **2**-front gable, **3**-rear, **4**-joining the four sides together, **5**-roof, **6**-vent, **7**-door, **8**-glazing, **9**-vent attachment, **10**-door attachment, **11** anchoring down, **12** optional louvre, **13** optional shelf, **14** optional staging, **15** finishing touches. If you need to contact us for assistance please refer to the relevant section/s. If your building is longer than 12', i.e. has an extension then please also refer the separate extension manual.

**Safety Warning**

- Glass and aluminium can potentially cause injury. Please ensure you wear protective goggles, gloves, headgear and suitable footwear when assembling and glazing the building.
- Please remember that glass is fragile and should be handled with extreme care. Always clear up and dispose of any breakages immediately.
- Do not assemble the greenhouse in high winds.
- For safety reasons and ease of assembly, we recommend that this greenhouse is assembled by a minimum of two people.
- Please clear all lying snow from the greenhouse roof as it can cause the roof to buckle or collapse.

**Site Preparation**

- When selecting a site for your greenhouse, it is vital that you choose as flat and level an area as possible.
- A concrete or slabbed base will provide the most solid foundation for your greenhouse.
- **IMPORTANT: Do not** fix your building down until the building is fully assembled, including glazing.
- Avoid placing your greenhouse under trees or in other vulnerable locations.
- To minimise the risk of wind damage, try to select as sheltered a site as possible, e.g. beside a hedgerow or garden fence.


**Additional Considerations**

- Please bear in mind that assembling your greenhouse can be time consuming. You may need to spread the construction over two or more days. We recommend that you avoid leaving the building partially glazed. If you ever have to leave your greenhouse half assembled and not anchored down, weigh it down with slabs or bags of sand to stop the wind moving it.
- You will find it helpful to prepare a large, clean and clear area in which to work in. A garage floor or flat lawn area is ideal.
- If you have arranged for someone to install your greenhouse for you, please check that all components are included. Some parts are numbered and can be identified by a stamped or hand written number (without the 'D'). Alternatively, the components can be identified by their distinctive profiles, lengths and quantities detailed in the parts list (see next page).
- Anchoring down your greenhouse should be the final stage of construction (including glazing).
- Once installed your greenhouse requires little maintenance, but to maintain the smooth running of your door(s) WD40 or similar can be applied to the door wheels and lower door guides.

**Guarantee**

- Your new Robinsons greenhouse is guaranteed for 10 years against faulty manufacture of the frame-work. This does not include glazing, moving parts, accidental damage or wind damage.

KEY SYMBOL	KEY DESCRIPTION
	EXTERNAL VIEW
	INTERNAL VIEW
	THINK
	THIS SECTION RELATES TO ANOTHER (e.g. 1 to 5)
	CORRECT
	DO <u>NOT</u> FIX DOWN!
	TWIST TO LOCK
	TIGHTEN
	PUSH AND HOLD
	CUT TO LENGTH



SECTION No	TITLE	ASSEMBLY SYNOPSIS: IMPORTANT INFORMATION / CONSIDERATIONS
	PARTS LIST	Most components should have a 'D' code punched into their metal surface. Identify and separate all like for like components prior to assembly. The 'parts list' also separates parts into the various sections shown below. Parts can also be identified by their profile pictures and stated lengths etc..
B	BASE	Base dimensions and recommendations. Ensure that your base is level as this will make assembly of the building, especially the glazing of the roof much more straight forward.
P	PREPARATION	Tools required. <b>IMPORTANT:</b> Use WD40 or similar in the glazing bar channels and insert the black glazing rubber prior to frame assembly.
1	SIDES	Take the side glazing bars 'D609' with the rubber inserted and the diagonal braces 'D604', use 10mm bolts to join them to the gutter and 15mm bolts to the cills (note how the head of the bolts slide into each glazing bar during construction).
2	FRONT	Again ensuring that the gable framework is rubbered-up follow the diagrams to assemble each end of the building. Make sure that you have inserted the extra bolts utilised in sections 4, 5 and 10. On the roof and side corner bars not every rubber channel will require rubber unless it is to be utilised in a partition (see separate manual and section P).
3	REAR	
4	JOINING THE FOUR SIDES	Take the two sides (1) and both gables (2 & 3) and join them together on your base. It is a good idea to tie some ladders to the sides to support them if you do not have anyone to hold them for you.
5	ROOF	Attach ridge and then the rubbered-up roof bars ensuring that they are fully butted up to the ridge and down onto the gutter. If you have <u>cresting</u> then it is a good idea to fit it before glazing, see section (15).
6a	VENT	Once the vent is glazed add silicone to the vent sides and top. Stand the vent/s on their hinge (vent top) and then leave the silicone to set.
6b	VENT SLAM	The slam bar 'D079' can be moved up and down between the roof glazing bars so that it can be butted down onto the pane of glass beneath, the autovent will be attached to it later on (9).
7	DOOR	Construct the door using the diagrams and then leave to one side ready for attachment in section (10).
8	GLAZING	Layout the bar capping and covers around the building like a sundial checking that all is present and correct. You can also place the roof capping in the gutters so they are closer to hand. The glass in the ends has to bevel on the black separator strip which this bevelling action allows the glass to tuck underneath the roof corner canopy. Use the capping and the self tapping screws to then hold the glass in place. The covers then enclose the screw heads giving a neat finish. A top tip is to not attach the door post capping (D766/D767) until you have fitted the door runner and threshold (10) to give you more room to manoeuvre. It is a good idea to glaze two roof sections first to ensure the building is square followed by two side sections to ensure the building isn't leaning,
9	VENT ATTACHMENT	Take the assembled vent and slide the vent hinge 'D866' into the end of the ridge allowing the vent the pivot open and closed. Vent stops go either side of the vent to stop any lateral movement (so insert stop / vent / stop). Attachment of the Bayliss XL autovents.
10	DOOR ATTACHMENT	Use the bolts inserted in section (2) to attach the upper door track. The lower door runner 'D860' and ramp threshold 'D087' push down and lock together.
11	ANCHORING DOWN	Now that the greenhouse is finished and the door and vent/s are operating without interference then you need to anchor the building down using 2" rawl plugs and screws. Use a 7mm masonry bit in a hammer drill to create the holes.
12	OPTIONAL LOUVRE	They attach to the building during the glazing process (8) like a piece of glass with a black separator above and below them.
13	OPTIONAL SHELIVING	Robinsons integral cantilever staging and shelving attaches to the inside of the greenhouse frame using either square head bolts (insert four into each side glazing bar 'D609' during construction of the sides (1)) or rectangular 'crop head' bolts which can be fitted retrospectively (both sets of bolts accompany the shelving/staging). This system allows the height of either the staging or the shelf to be set at an operator specific height. Commonly the staging brackets are set 900mm from the cills though you can alter this to suit the end user/s. The aluminium shelf / staging slats come in two lengths; (4'):1240mm 'D2002' and (6'):1860mm 'D2003'. These slats can combine to create any length of staging required, i.e. 4'+6' = 10' etc...
14	OPTIONAL STAGING	
15	FINISHING TOUCHES	Now that the main body of the structure is complete you can add; ridge caps, downpipe fittings, eave bungs. Images showing cresting and finial attachment, this is often easiest to do after section (5) rather than using the vent apertures later on (i.e. before glazing).

Section Ref	Part No.	Section	Size (mm)	5 4	5 6	5 8	5 10	5 12
-------------	----------	---------	-----------	-----	-----	-----	------	------

<b>1</b>	D071		1274	2					
	D043		1894		2				
	D021		2514			2			
	D022		3134				2		
	D023		3754					2	
	D070		1277	2					
	D042		1897		2				
	D014		2517			2			
	D015		3137				2		
	D016		3757					2	
	D604		1316	4					
	D609		1160	2	4	6	8	10	
RUBBER		1000 (1m)	5	10	14	19	24		
D174		N/A	2	4	4	8	8		

<b>2</b> <b>+</b> <b>3</b>	DV301L					1		
	DV301R		537			1		
	D628		650			1		
	D756		1670			1		
	D788		1986			2		
	D785		1386			2		
	D608		1160			4		
	D789		1250			4		
	D111		N/A			2		
	D750					2		
	D751		882			2		
	RUBBER		1000 (1m)			27		
	D174		N/A			8		

Section Ref	Part No.	Section	Size (mm)	5 4	5 6	5 8	5 10	5 12
-------------	----------	---------	-----------	-----	-----	-----	------	------

<b>5</b>	D072		1277	1				
	D044		1897		1			
	D001		2517			1		
	D002		3137				1	
	D003		3757					1
	D752		882	2	4	6	8	10
	RUBBER		1000 (1m)	4	8	11	15	18

<b>6</b>	D866		639	1	1	2	3	4
	D863L		613	1	1	2	3	4
	D863R		613	1	1	2	3	4
	D862		593	1	1	2	3	4
	D079 PLUS FLUFF		590	1	1	2	3	4
	D114		N/A	2	2	4	6	8
	D220 PLUS FS6060 SCREW		N/A	2	2	4	6	8
	D205		N/A	2	2	4	6	8

## Regatta DWARF

MAIN FRAME QUANTITIES VENTS / DOORS etc SEPERATE		10mm	22	28	34	40	46
		15mm	36	40	42	44	46
		m6	58	68	76	84	92

Section Ref	Part No.	Section	Size (mm)	5 4	5 6	5 8	5 10	5 12
-------------	----------	---------	-----------	-----	-----	-----	------	------

<b>7</b>	D762 + D347 lock = D764		1714			1		
	D763 + D156 strike = D765		1714			1		
	D760		1714			1		
	D761		1714			1		
	D059+ D217 wheel = D060		305			2		
	D061		305			2		
	D062		305			2		
	D233		797			8		
	P053		N/A			2		
	D225		610			1 CUT		
	D840 B		4000			1		
	D263 Pack Of 7		N/A			14		
			N/A			14		
D260 pack		N/A			24			

Section Ref	Part No.	Section	Size (mm)	5 4	5 6	5 8	5 10	5 12
-------------	----------	---------	-----------	-----	-----	-----	------	------



<b>8</b>	1	D618		1144	2	4	6	8	10
	5	D754		892	2	4	6	8	10
	3	D786		1391			2		
	2	D819		227			2		
	2/3	D610		1160			4		
	1	D620		1144			4		
	5	D753		892			4		
	2	D766		1773			2		
	2/3	D614		1162			4		
	1	D619		1144	6	8	10	12	14
	5	D755		892	6	8	10	12	14
	2	D767		1773			2		
	3	D787		1391			2		
2	D846		229			2			

<b>10</b>	D864		590			1		
	D860		1240			1		
	D087		587			1		
	D082		1270			1		
	D081		1270			1		
	D163		90			2		
	D150		N/A			1		
	D222 /B		590			1		
	D204 L&R /B					1 + 1		
	D845					2		
	D312					2		

Regatta DWARF

**THIS PLAN APPLIES TO GREENHOUSES WITH DOORS AT ONE END ONLY.**

50mm MINIMUM



GREENHOUSE TYPE	OVER ALL WIDTH 'W'	BRICKWORK RETURN DIMENSION 'X'	OVER ALL LENGTH 'L' = BASIC GREENHOUSE LENGTH + EXTENSION IF REQUIRED	
			BASIC GREENHOUSE LENGTH	EXTENSION LENGTH
REGATA (5 WIDTH)	1654mm	497mm	6 LONG	6ft EXT LONG
REGENT (6 WIDTH)	1960mm	650mm	8 LONG	8ft EXT LONG
ROYALE (8 WIDTH)	2580mm	650mm	10 LONG	10ft EXT LONG
ROSETTE (10 WIDTH)	3210mm	965mm	12 LONG	12ft EXT LONG
REGAL (12 WIDTH)	3820mm	1270mm		
RENOWN (14 WIDTH)	4450mm	1585mm		

**GUIDANCE NOTE FOR ROBINSONS DWARF WALL GREENHOUSES. FOOTINGS**  
CONCRETE STRIP FOOTINGS SHOULD BE A MINIMUM OF 400mm WIDE X 200mm DEEP. IF THE SITE IS ON MADE UP GROUND IT IS IMPORTANT THAT THE FOOTINGS ARE CUT INTO THE COMPACTED GROUND BELOW.

WHERE THE GROUND IS LIABLE TO MOVEMENT SUCH AS HEAVY CLAY OR LOOSE SANDY SOIL REINFORCING SHOULD BE ADDED TO THE CONCRETE FOOTINGS.

**WALLS**  
IT IS MOST IMPORTANT THAT THE BRICKWORK IS IN ACCORDANCE WITH THE DIMENSIONS PROVIDED AND IS SQUARE, LEVEL, AND UPRIGHT. THE DIAGONAL MEASUREMENTS SHOULD BE EQUAL.

WALLS CAN BE EITHER DOUBLE OR SINGLE SKIN.

THE TOP COURSE OF BRICKS SHOULD BE LAID FROG DOWN. IF ENGINEERING BRICKS ARE USED FOR THE TOP COURSE, PLEASE ENSURE THEY ARE SOLID NOT CELLULAR (WITH HOLES THROUGH THEM) OR FIXING DOWN OF THE GREENHOUSE WILL BE A PROBLEM. BRICKS SHOULD BE A GOOD QUALITY STOCK BRICK. SAND FACED FLETTON TYPE BRICKS ARE NOT SUITABLE.

**GABLE DOOR OPENING**


THE DOOR THRESHOLD REQUIRES BRICK WORK ACROSS THE OPENING WHICH SHOULD BE LEVEL WITH THE FINISHED FLOOR LEVEL (F.F.L.) OF THE GREENHOUSE

THE OPENING FOR THE DOORWAY AND THE HEIGHT TO THE TOP OF THE WALL FROM THE THRESHOLD LEVEL REQUIRE THE HIGHEST ACCURACY AND ARE MOST IMPORTANT SO THAT THE DOOR FITS THE APERTURE CORRECTLY. IT IS ADVISABLE TO MAKE A WOODEN TEMPLATE TO CHECK THE DOOR APERTURE DIMS.


IF SINGLE SKIN WALLS ARE USED THEN PIERS SHOULD BE FORMED AT THE DOOR OPENING.

IN ORDER TO SUPPORT THE OUTER EDGE OF THE DOOR THRESHOLD THERE MUST BE A PROJECTION OF BRICKWORK / CONCRETE IN FRONT OF THE DOOR END WALL WITH A MINIMUM WIDTH OF 50mm. THIS NEEDS TO BE LEVEL WITH THE DOOR THRESHOLD OPENING.

Property of 'Robinsons Greenhouses' © 2015







TITLE: **GREENHOUSE DWARF WALL PLAN**



Feed glazing rubber into each glazing bar and trim to length. Notice that some channels are only used on a partition. Applying a lubricant to the aluminium channels will speed up insertion.



e.g.



The frame is assembled by feeding square headed bolts, either 10mm or 15mm in length into the slots on glazing bars and then locating those bolts through holes in purlings and cills, etc... Twist in (rectangular) crop headed bolts are also used towards the end of construction to attach components to the frame when the glazing bar slots are no longer exposed at the ends.








15mm




10mm

e.g.






4 X 2 DWARF		
Part No	mm	Quantity
D070	1277	2
D071	1274	2
D609	1160	2
D604	1316	2
D174		2
M6-10mm		2
M6-15mm		4
M6-NUT		6
Rubber	1000	5




6 X 2 DWARF		
Part No	mm	Quantity
D042	1897	2
D043	1894	2
D609	1160	4
D604	1316	4
D174		4
M6-10mm		4
M6-15mm		8
M6-NUT		12
Rubber	1000	10

e.g. ①




8 X 2 DWARF		
Part No	mm	Quantity
D014	2517	2
D021	2514	2
D609	1160	6
D604	1316	4
D174		4
M6-10mm		6
M6-15mm		10
M6-NUT		16
Rubber	1000	14

e.g. ②






10 X 2 DWARF		
Part No	mm	Quantity
D015	3137	2
D022	3134	2
D609	1160	8
D604	1316	4
D174		8
M6-10mm		8
M6-15mm		12
M6-NUT		20
Rubber	1000	19




12 X 2 DWARF		
Part No	mm	Quantity
D016	3757	2
D023	3754	2
D609	1160	10
D604	1316	4
D174		8
M6-10mm		10
M6-15mm		14
M6-NUT		24
Rubber	1000	24

















Part No	mm	Quantity
DV301L	537	1
DV301R	537	1
D608	1160	2
D628	650	1
D750	882	1
D751	882	1
D788	1986	2
D789	1250	2

Part No	mm	Quantity
D111		1
D174		4
D227		15m
M6X10		8
M6X15		14
M6NUT		22


















Part No	mm	Quantity
D608	1160	2
D750	882	1
D751	882	1
D756	1670	1
D785	1386	2
D789	1250	2

Part No	mm	Quantity
D111		1
D174		4
D227		12m
M6X10		8
M6X15		10
M6NUT		18



**3**








4'		
Part	mm	Quan.
D072	1277	1
D752	882	2
RUBBER	1000	4

6'		
Part	mm	Quan.
D044	1897	1
D752	882	4
RUBBER	1000	8


8'		
Part	mm	Quan.
D001	2517	1
D752	882	6
RUBBER	1000	11

10'		
Part	mm	Quan.
D002	3137	1
D752	882	8
RUBBER	1000	15

12'		
Part	mm	Quan.
D003	3757	1
D752	882	10
RUBBER	1000	18





**5**



D1208  
1 of -  
610 x 610  
pane




Part No		mm	Quantity
D866		639	1
D863L		613	1
D863R		613	1
D862		593	1

Part No		mm	Quantity
D220 PLUS FS6060 SCREW		N/A	2
D205		N/A	2
SY-BOLM6X11		10	4
SYNUTM6		M6	4
8 X 12 S/T FS6017		10	2
8 x 19 S/T FS6018		19	2









6a






1 vent  
slam bar = {

Part No		mm	Quantity
SY-BOLM6X11		10	2
SY-BOLM6X15		15	2
SYBOLM6 X11CROP		10	2
SYNUTM6		N/A	4




Part No		mm	Quantity
D079 PLUS FLUFF		590	1
D114		N/A	2


6



6b






















Part No		mm	Q
D762 + D347 lock = D764		1714	1
D763 + D156 strike = D765		1714	1
D760		1714	1
D761		1714	1
D059+D217 wheel = D060		305	2
D061		305	2
D062		305	2

Part No		mm	Q
D233		797	8
P053		N/A	2
D225		610 (cut 2 x 305)	1
D840B		4000	1
D263 PACK x 2		N/A	14
		N/A	14
D261 PACK		N/A	24










PART No	Section	Size (mm)	e.g.
D618		1144	
D754		892	
D786		1391	
D819		227	
D610		1160	
D620		1144	
D753		892	
D766		1773	
D614		1162	
D619		1144	
D755		892	
D767		1773	
D787		1391	
D846		229	





# REGATTA DWARF TOUGHENED GLASS





e.g. 5x8





PART No		Size (mm)	4'	6'	8'	10'	12'	
D1216	S	610 X 1162	4	6	8	9	11	
D775	R	610 X 900	3	5	6	7	8	
D1208	A	610 X 610	1	1	2	3	4	
D1254	U	610 X 305	1	1	2	3	4	
D909	C	247 X 812					4	
D769	T	457 X 1162					4	
D772	X	ANGLE					4	
D768	Y	APEX					1	
D773	Z	APEX					1	
D222/B		590 long					1	
D101 / ROSEPS	H	610 long					5	










D624	M	610 X 550	1
D729	L	525 X 100	6
D101 / ROSEPS	H	610 long	1





















Part No		mm	Q
D864		590	1
D082		1270	1
D081		1270	1

Part No		mm	Q
D163		90	2
D150			1
D845			2
SY-BOLM6X15			8
SYNUTM6			8







**10**















**10**



Part No		Quantity
D860		1
D087		1




5







Part No		Quantity
D312		2
D222/B		590
D204L/B		1
D204R/B		1





Please note that the lengths of D819 / D846 may need cutting slightly shorter depending on height of the door track assembly.









11












OPTIONAL  
louvre = {

Part No		mm	Quantity
D168L		552	1
D168R (handle)		552	1
D165		612	2
D166		552	2
FS6013		12	4










Example: 2x 4' 3 slat shelves 'ST0304' = 8' run



13







Example: 2x 4' **5 slat** staging 'ST0504' = 8' run






note  
D2003 = 1860mm

14



# OPTIONAL crestring = {

- End finials need to be pinched onto ridge using 'DV282' grub screws.
- Depending on your ridge length a half crestring may need to be cut or/ and some spacer bar 'DV281' cut into two equal sections.
- Each finial and crestring piece needs to be siliconed 'D119' into place.



Please be aware that this is a multi-national manual, if you spot any errors or have any constructive comments regarding the manual please email [james.spooner@greenhousepeople.co.uk](mailto:james.spooner@greenhousepeople.co.uk) and I will make the necessary amendments. Whilst the information contained in this booklet is accurate at the time of publication, changes in the course of Robinsons policy of improvement through development and design might not be indicated. We point out this fact to avoid any infringements of the Trade Descriptions Act and also to advise that Robinsons Greenhouses reserve the right to change specifications and materials without prior notice.

In addition any photographs of completed buildings would be most appreciated to add to our portfolio.

## Here's how you can earn £30 and have your new greenhouse feature in our next brochure....

We are always interested to hear how you went on assembling your greenhouse, and we are particularly interested to see photos of the finished article.

We like to see where you've put it, how you're using it and how it looks in your garden. Often we glean ideas from this which we can pass on to other gardeners as useful tips.

It is always nice if we can include 'real' greenhouse photos in the brochure, so if you send us a photo of your greenhouse to us and it is good enough to get into our next brochure, **we will send you a £30 reward.**

**Please send your photos to:**

**Photo competition**

**Robinsons Greenhouses**

**Blythe Park**

**Cresswell**

**Stoke-on-Trent**

**Staffs**

**ST11 9RD**

**Or better still, email us on [james.durose@greenhousepeople.co.uk](mailto:james.durose@greenhousepeople.co.uk)**

Please write on the reverse of photos your name and address and if you would like them back, please write 'please return' on them too.

**We wish you all the best with your new greenhouse, and we look forward to seeing your photos in the near future!**

THIS GREENHOUSE BOX WAS PACKED BY: \_\_\_\_\_

DATE: \_\_\_\_\_



[www.robinsonsgreenhouses.co.uk](http://www.robinsonsgreenhouses.co.uk)

To contact Robinsons Customer Services email us at [sales@robinsonsgreenhouses.co.uk](mailto:sales@robinsonsgreenhouses.co.uk) or call us on 01782 385 409.

Our address is Robinsons Greenhouses, Unit 19 Blythe Park, Cresswell, Stoke-on-Trent, Staffordshire, ST11 9RD